


REMARKS

Claims 1-20 are pending. By this Supplemental Preliminary Amendment, claims 1-20 are amended. The specification and Abstract are replaced with a Substitute Specification and Substitute Abstract. No new matter has been added.

The attached Appendix includes marked-up copies of the specification (37 C.F.R. §1.125(b)(2)) and each rewritten claim (37 C.F.R. §1.121(c)(1)(ii)).

Prompt and favorable examination on the merits is respectfully requested.

Respectfully submitted,



James A. Oliff
Registration No. 27,075

Eric D. Morehouse
Registration No. 38,565

JAO:EDM/gam

Attachments:

Substitute Abstract
Appendix
Substitute Specification
Marked-up copy of specification

Date: March 11, 2002

OLIFF & BERRIDGE, PLC
P.O. Box 19928
Alexandria, Virginia 22320
Telephone: (703) 836-6400

DEPOSIT ACCOUNT USE AUTHORIZATION Please grant any extension necessary for entry; Charge any fee due to our Deposit Account No. 15-0461
--

APPENDIX

Changes to Abstract:

The following is a marked-up version of the amended Abstract.

ABSTRACT OF THE DISCLOSURE

~~{Object}~~ To The invention provides an organic electroluminescent element driving circuit to which a reverse-bias is applied, ~~with neither~~ which does not require a substantial increase in power consumption ~~nor an~~ increase in layout space ~~involved~~.

~~—— [Solving Means]~~ With switches ~~20-1~~ and ~~20-2~~ arranged, electroluminescent elements are set to be in a reverse-bias state. The pixels are reverse-biased on the basis of a group of predetermined pixels at a time, for example, the pixels are reverse-biased on a pixel-by-pixel basis or on a line-by-line basis, or all pixels are reverse-biased at a time. In this way, reverse bias can be applied without the need for an additional power source, and ~~with neither~~ without requiring a substantial increase in power consumption ~~nor an~~ increase in layout space ~~involved~~. The service life of the organic electroluminescent element can thus be prolonged.

Changes to Specification:

A Substitute Specification is attached in accordance with 37 C.F.R. 1.125(b)(2).

Changes to Claims:

The following are marked-up versions of the amended claims:

1. (Amended) A driving circuit for actively driving an organic electroluminescent display device in which a plurality of pixels, each containing an organic electroluminescent element, are arranged in a matrix, the driving circuit comprising:
——-a reverse-bias setting circuit which sets the organic electroluminescent elements to a reverse-bias state on an area-by-area basis.

2. (Amended) A driving circuit for actively driving an organic electroluminescent display device in which a plurality of pixels, each containing an organic electroluminescent element, are arranged in a matrix, the driving circuit comprising:-

_____ a reverse-bias setting circuit which sets organic electroluminescent elements contained in a predetermined area, from among the organic electroluminescent elements, to a reverse-bias state.

3. (Twice Amended) ~~A-The~~ driving circuit according to claim 1, ~~wherein~~ the reverse-bias setting circuit ~~comprises~~ including a switch which switches an electrical connection state of at least one of electrodes of each of the organic electroluminescent elements between being connected to a first power source line ~~for that~~ supplying a first potential and being connected to a second power source line ~~for that~~ supplying a second potential that is lower in level than the first potential.

4. (Twice Amended) ~~A-The~~ driving circuit according to claim 1, ~~wherein~~ the reverse-bias setting circuit ~~comprises~~ including a switch which switches an electrical connection state of a cathode of each of the organic electroluminescent elements between being connected to a first power source line ~~for that~~ supplying a first potential and being connected to a second power source line ~~for that~~ supplying a second potential that is lower in level than the first potential.

5. (Twice Amended) ~~A-The~~ driving circuit according to claim 3, ~~wherein~~ the switches ~~are-being~~ arranged with one switch for each pixel, so that the organic electroluminescent elements ~~are-being~~ set to be in a reverse-bias state on a pixel-by-pixel basis by controlling the switches.

6. (Twice Amended) ~~A-The~~ driving circuit according to claim 3, ~~wherein~~ the switches ~~are-being~~ arranged with one switch for each line of pixels, so that the organic electroluminescent elements are set to be in a reverse-bias state on a line-by-line basis by controlling the switches.

7. (Twice Amended) ~~A-The~~ driving circuit according to claim 3, ~~wherein~~ the switch ~~is-being~~ arranged with a single switch for all pixels, so that the organic

electroluminescent elements for all pixels are set to be in a reverse-bias state by controlling the switch.

8. (Twice Amended) ~~A The~~ driving circuit according to claim 3, ~~wherein the switches are being~~ arranged with one switch for each of particular pixels, so that only the organic electroluminescent elements for the particular pixels are set to be in a reverse-bias state by controlling the switches.

9. (Amended) A driving circuit for driving an electro-optical device in which a plurality of electro-optical elements are arranged in a matrix, the driving circuit comprising:
- _____ a reverse-bias setting circuit which sets at least one of the electro-optical elements to a reverse-bias state.

10. (Twice Amended) ~~A piece of Electronic~~ electronic equipment, comprising:
- _____ an active-matrix display device ~~mounted therein~~ that includes the driving circuit according to claim 1.

11. (Amended) An electro-optical device, comprising:
- _____ ~~a driving circuit for actively driving a display device in which~~ that includes a plurality of pixels, each of the plurality of pixels including an electro-optical element, ~~are arranged in a matrix;~~ and
_____ a driving circuit that drives the display device; the driving circuit ~~comprising~~ including a reverse-bias setting circuit which sets the electro-optical elements to a reverse-bias state on a predetermined area-by-area basis.

12. (Amended) An electro-optical device, comprising: ~~a driving circuit for actively driving~~
_____ a display device in which that includes a plurality of pixels, each of the plurality of pixels including an electro-optical element, ~~are arranged in a matrix;~~ and

a driving circuit that drives the display device, the driving circuit comprising
including a reverse-bias setting circuit which sets electro-optical elements contained in a predetermined area, from among the electro-optical elements, to a reverse-bias state.

13. (Twice Amended) ~~An~~ The electro-optical device according to claim 11, ~~wherein~~ the reverse-bias setting circuit ~~comprises~~ including a switch which switches an electrical connection state of at least one of electrodes of each of the electro-optical elements between being connected to a first power source line ~~for that~~ supplying a first ~~potential~~ potential and being connected to a second power source line ~~for that~~ supplying a second ~~potential~~ potential that is lower in level than the first ~~potential~~ potential.

14. (Twice Amended) ~~An~~ The electro-optical device according to claim 11, ~~wherein~~ the reverse-bias setting circuit ~~comprises~~ including a switch which switches an electrical connection state of a cathode of each of the electro-optical elements between being connected to a first power source line ~~for that~~ supplying a first ~~potential~~ potential and being connected to a second power source line ~~for that~~ supplying a second ~~potential~~ potential that is lower in level than the first ~~potential~~ potential.

15. (Twice Amended) ~~An~~ The electro-optical device according to claim 13, ~~wherein~~ the switches ~~are being~~ arranged with one switch for each pixel, so that the electro-optical elements are set to be in a reverse-bias state on a pixel-by-pixel basis by controlling the switches.

16. (Twice Amended) ~~An~~ The electro-optical device according to claim 13, ~~wherein~~ the switches ~~are being~~ arranged with one switch for each line of pixels, so that the electro-optical elements are set to be in a reverse-bias state on a line-by-line basis by controlling the switches.

17. (Twice Amended) ~~An~~ The electro-optical device according to claim 13, ~~wherein~~ the switch ~~is being~~ arranged with a single switch for all pixels, so that the ~~organic~~

~~electroluminescent~~electro-optical elements for all pixels are set to be in a reverse-bias state by controlling the switch.

18. (Twice Amended) ~~An~~The electro-optical device according claim 13, ~~wherein~~ the switches ~~are being~~ arranged with one switch for each of particular pixels, so that only the electro-optical elements for the particular pixels are set to be in a reverse-bias state by controlling the switches.

19. (Amended) An electro-optical device, comprising: ~~a driving circuit for driving~~
_____ a plurality of electro-optical elements ~~arranged in a matrix;~~ and
_____ a driving circuit that drives the plurality of electro-optical elements, ~~wherein~~ the driving circuit ~~comprises including~~ a reverse-bias setting circuit which sets at least one of the plurality of electro-optical elements to a reverse-bias state ~~on an area-by-area basis.~~

20. (Twice Amended) ~~An~~The electro-optical device according to claim 11, ~~wherein~~ the electro-optical element ~~is being~~ an organic electroluminescent element.